



**COUGAR**

[www.sumotire.com](http://www.sumotire.com)



# TRUCK & BUS RADIAL *Tires*

# Engineered for Optimal Performance



## SSR06

*Designed and built for steering and trailer application*

- Advance 21/32nds tread design to help water drainage, minimise irregular wear, promotes long life with smooth even wear, ideal for Regional and Pick-up & Delivery fleets

INFLATED NEW TYRE DIMENSIONS								
Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD (32nd)	Rim Width
295 / 75R22.5	TL	144 / 141M (146 / 143L)	14, 16	40.2	11.7	9.3	22 / 32	9
285 / 75R24.5	TL	144 / 141M (147 / 144L)	14, 16	41.5	11.1	9.3	22 / 32	8.25
11R22.5	TL	144 / 142M (146 / 143L)	14, 16	41.5	11.0	8.9	22 / 32	8.25
11R24.5	TL	146 / 143M (149 / 146L)	14, 16	43.5	11.0	9.0	22 / 32	8.25



## SSD09

*Designed and built for driving position*

- Mega deep 30/32nds tread for long original life
- Supported by strong block and solid shoulder to resist tread squirm and irregular wear
- Advance tread compound for better traction, handling, mileage and uniform wear



INFLATED NEW TYRE DIMENSIONS								
Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD (32nd)	Rim Width
295 / 75R22.5	TL	144 / 141M (146 / 143L)	14, 16	40.4	11.7	8.9	30 / 32	9
285 / 75R24.5	TL	144 / 141M (147 / 144L)	14, 16	42.0	11.1	9.0	30 / 32	8.25
11R22.5	TL	144 / 142M (146 / 143L)	14, 16	41.9	11.0	8.9	30 / 32	8.25
11R24.5	TL	146 / 143M (149 / 146L)	14, 16	43.9	11.0	8.9	27 / 32	8.25



## SSR511

*Designed and built for trailer application*

- Tread depth 14/32nds for trailer use
- Supported by mini sipings to prevent river wear
- Advance tread compound for better handling, better mileage and uniform wear

INFLATED NEW TYRE DIMENSIONS								
Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD (32nd)	Rim Width
295 / 75R22.5	TL	144 / 141L (146 / 143L)	14, 16	40.2	11.7	8.7	14 / 32	9
285 / 75R24.5	TL	144 / 141L (147 / 144L)	14, 16	41.6	11.1	8.7	14 / 32	8.25
11R22.5	TL	144 / 142L (146 / 143L)	14, 16	41.5	11.0	7.9	14 / 32	8.25
11R24.5	TL	146 / 143L (149 / 146L)	14, 16	43.5	11.0	8.7	14 / 32	8.25



All measurements are in inches



Recommended



Optional



Not suitable



19 Lok Yang Way, Jurong, Singapore 628635

Tel: +65 6268 3111 • Fax: +65 6264 148

Email: sales@sumotire.com • Website: www.sumotire.com