



MADE IN THAILAND



Long Haul / Regional Application

SR505

SD808





SR505

- › Excellent handling for maximum safety through customized tread pattern and casing design.
- › Optimum tread radius thanks to equal 5 rib design for even wear.
- › 4 breaker construction gives smooth handling and protects casing for retreading.
- › Special tread grooves enhance resistance to stone retention, and thus minimizing casing damage.
- › Reduced rolling resistance and low fuel consumption due to special tread compounds.

- › Wide tread and special tread compound for long mileage.
- › Solid shoulder construction with zero angle steel band ply protects shoulder from irregular wear.
- › Specially formulated compound and extra block siping provide maximum wet grip.
- › Highly durable casing construction allows for multiple retreads.



SD808

Technical data and recommended Tyre pressure

Size	Pattern	PR	LI & SS	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Recommended Rim Width (inches)
215/75R17.5	SR505	16	135/133J	767	212	12.5	6.00
	SD808			767		14.0	
235/75R17.5	SR505	18	143/141J	797	233	13.0	6.75
	SD808			797		14.5	
295/80R22.5	SR505	18	154/149L	1044	298	14.0	9.00
	SD808			1044		17.0	
315/80R22.5	SR505	20	156/150L	1076	312	14.5	9.00
	SD808			1076		18.5	

