

TRUCK & BUS

RADIAL TYRES



19 Lok Yang Way, Jurong Singapore 628635

T: +65 6268 3111

F: +65 6264 0148

E: sales@sumotire.com

W: www.sumotire.com

For business partners:

TITANO

Series

DRIVEN TO PERFECTION

SUMO FIRENZA tyres not offered or available for sale in the USA.





TITANO-MS1

- DESIGNED AND BUILT FOR ALL POSITION
- UNIQUE TREAD DESIGN PROVIDES EXCELLENT TRACTION ON BOTH ON & OFF ROADS
- RIB / BLOCKS DESIGN SUITABLE FOR ALL POSITION AXLES FOR HARSH CONDITIONS
- STONE REJECTOR DESIGN TO PROTECT GROOVE FROM PUNCTURING
- THICK SIDEWALL TO PROTECT FROM SIDEWALL IMPACTS CONDITIONS
- 18PR RATED FOR HIGH LOAD CARRYING CAPACITY



MADE IN THAILAND

Size	Service Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim Width (mm)	Max. Load Capacity at Cold inflation Pressure					
							Single		Dual		Pressure	
							(kg)	(LBS)	(kg)	(LBS)	(kpa)	(PSI)
10.00R20	149/146K	18PR	1054	278	14.5	7.5	3250	7160	3000	6610	930	135



TITANO-D4

- DESIGNED AND BUILT FOR DRIVING POSITION
- UNIQUE TREAD DESIGN PROVIDES EXCELLENT TRACTION ON BOTH DRY AND WET CONDITIONS
- 4 RIB / BLOCK TREAD DESIGNED TO MAXIMIZE MILEAGES IN HARSH CONDITIONS
- "IN GROOVE" STONE EJECTORS TO MINIMIZE TREAD PUNCTURING
- 18PR RATED FOR HIGH LOAD CARRYING CAPACITY



MADE IN THAILAND

Size	Service Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim Width (mm)	Max. Load Capacity at Cold inflation Pressure					
							Single		Dual		Pressure	
							(kg)	(LBS)	(kg)	(LBS)	(kpa)	(PSI)
10.00R20	149/146J	18PR	1063	278	19	7.5	3250	7160	3000	6610	930	135



TITANO-D3

- DESIGNED AND BUILT FOR DRIVING POSITION
- WIDELY USED FOR HIGHWAY AND LIGHT UNPAVED ROAD CONDITIONS
- IMPROVED SHOULDER BLOCKS TO REDUCE SHOULDER DAMAGES
- DESIGNED FOR LASTING GRIP AND STABILITY
- 18PR RATED FOR HIGH LOAD CARRYING CAPACITY



MADE IN THAILAND

Size	Service Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim Width (mm)	Max. Load Capacity at Cold inflation Pressure					
							Single		Dual		Pressure	
							(kg)	(LBS)	(kg)	(LBS)	(kpa)	(PSI)
10.00R20	149/146K	18PR	1054	278	17.5	7.5	3260	7160	3000	6610	930	135



TITANO-DX6

- DESIGNED AND BUILT FOR DRIVING POSITION
- DELIVERS OUTSTANDING TRACTION FOR LONG HAUL AND DURABILITY
- DEEPENED TREAD DEPTH FOR EXCELLENT WATER EVACUATION.
- DESIGNED FOR LONG LASTING GRIP CAPABILITY, BRAKING AND STABILITY.
- 18PR RATED FOR HIGH LOAD CARRYING CAPACITY



MADE IN VIETNAM

Size	Service Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim Width (mm)	Max. Load Capacity at Cold inflation Pressure					
							Single		Dual		Pressure	
							(kg)	(LBS)	(kg)	(LBS)	(kpa)	(PSI)
10.00R20	149/146K	18PR	1061	271	18.5	7.5	3250	7160	3000	6610	930	135