

DRIVUS SERIES

DRIVEN TO PERFECTION



TRUCK & BUS
RADIAL TYRES



MADE IN
THAILAND



Phone Number
+65 62683111

Fax
+65 62640148

Address
19 Lok Yang Way, Jurong
Singapore 628635

Email
sales@sumotire.com

SUMO FIRENZA tyres are not offered or available for sale in the USA



DRIVUS-S

Excellent handling for maximum safety through customized tread pattern and casing design

Specially formulated tread compound minimizes heat problem for long-haul highway operations

Low rolling resistance construction and special compound brings fuel savings to customers

SIZE	PR	LL	SS	OVERALL DIAMETER MM	SECTION WIDTH MM	TREAD DEPTH MM	RECOMMENDED RIM WIDTH INCHES
295 / 60R22.5	16	150 / 147	L	926	292	13.0	9.00
315 / 60R22.5	16	152 / 148	L	950	313	14.5	9.75
315 / 70R22.5	16	154 / 150 (152 / 148)	L (M)	1014	312	15.0	9.00
315 / 80R22.5	20	156 / 150 (154 / 150)	L (M)	1076	312	15.5	9.00

SIZE	PR	LL	SS	OVERALL DIAMETER MM	SECTION WIDTH MM	TREAD DEPTH MM	RECOMMENDED RIM WIDTH INCHES
295 / 60R22.5	16	150 / 147	L	926	292	16.0	9.00
315 / 60R22.5	16	152 / 148	L	950	313	16.5	9.75
315 / 70R22.5	18	156 / 150 (154 / 150)	L (M)	1014	312	16.5	9.00
315 / 80R22.5	20	156 / 150 (154 / 150)	L (M)	1076	312	17.0	9.00

DRIVUS-D

Fuel-efficient drive radial designed for single and tandem-axle applications in long-haul and regional service

Shoulder blocks are reinforced by tie-bar to fight irregular wear and help grip the road; thus extending tread life

Low rolling resistance casing profile and energy saving sidewall compounds allow for fuel efficiency





DRIVUS-T

6 straight rib design with minimum sips ensure even wear to enhance long tyre life

Wide steel-belt construction braces the tread and high-resilient filler balances stiffness of the casing for improved durability

Designed to improve the low rolling resistance and fuel efficiency

SIZE	PR	LL	SS	OVERALL DIAMETER MM	SECTION WIDTH MM	TREAD DEPTH MM	RECOMMENDED RIM WIDTH INCHES
385 / 55R19.5	18	156	J	919	386	12.5	12.25
385 / 55R22.5	20	160 (158)	K (L)	996	386	12.0	12.25
385 / 65R22.5	24	164 (150)	K (L)	1072	389	13.5	11.75
435 / 50R19.5	20	160	J	931	438	12.5	14.00
445 / 45R19.5	20	160	J	895	446	12.5	15.00

