

TRUCK & BUS

RADIAL TYRES



SUPERIOR PERFORMANCE
TOTAL TRUST

APPLICATION CHART

	Steer (All Axle)	Drive	Trailer
LONG HAUL 	SSR05A SSR05 SSR05B SSM07/SSM07A SSR055A / SSR55A+	SSD08 SSD08B SST066 SSM07/SSM07A	SSR065 SST066 SSM07/SSM07A
REGIONAL 	SSR05A SSR05 SSR05B SSM07/SSM07A SSR055A / SSR55A+	SSD08 SSD08B SST066 SSM07/SSM07A	SSR065 SST066 SSM07/SSM07A
URBAN 	SSU05 SSU500	SSU05 SSU500	
ON/OFF 		SSM10 SST22	
OFF 	SML68 SML68A SML68XL SML68B	SML68 SML68A SML68XL SML68B	

CONTENTS

Application Chart	2
SSR05A	4
SSR05	5
SSR05B	5
SSD08	6
SSD08B	6
SSM10	7
SST22	7
SSR055A/SSR55A+	8
SSR065	8
SST066	9
SSM07/SSM07A	9
SSU05	10
SSU500	10
SML68/SML68A	11
SML68XL/SML68B	11

THE NEW REVOLUTION

TRUCK & BUS

RADIAL






SSR05A

DESIGNED AND BUILT FOR STEERING AND TRAILER APPLICATION

- Excellent handling for maximum safety through customized tread pattern and casing design
- Maximized life expectancy and uniform wear through even pressure distribution in the ground contact patch
- Reduced rolling resistance and low fuel consumption, due to special tread compounds
- Featured groove design avoids stone trapping

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
1000R20	TT	146 / 143L	16	1052	275	214	15	7.50
1100R20	TT	150 / 147L	18	1082	286	223	15.5	8.00
1200R20	TT	154 / 151L	18	1122	313	238	15.5	8.50
11R22.5	TL	148 / 145M	16	1052	279	210	15	8.25
12R22.5	TL	152 / 148M	16	1084	300	226	16	9.00
295 / 60R22.5	TL	149 / 146L	16	926	292	247	15	9.00
315 / 60R22.5	TL	152 / 148L	16	950	313	272	15.3	9.75
245 / 70R19.5	TL	136 / 134M (141 / 140J)	14	839	248	190	13.5	7.50
265 / 70R19.5	TL	140 / 138M (143 / 141J)	14	867	262	208	14	7.50
275 / 70R22.5	TL	148 / 145M	16	962	275	236	15	8.25
315 / 70R22.5	TL	152 / 148M (154/150L)	18	1014	312	272	15	9.00
295 / 80R22.5	TL	152 / 148M	16	1050	298	250	15	9.00
315 / 80R22.5	TL	156 / 150L (154/150M)	20	1080	312	254	15	9.00





SSR05

Long Haul / Regional Application, Steer Axle

- Excellent handling for maximum safety through customized tread pattern and casing design
- Maximized life expectancy and uniform wear through even pressure distribution in the ground contact patch
- Reduced rolling resistance and low fuel consumption, due to special tread compounds

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
215 / 75R17.5	TL	126 / 124L	16	767	212	168	12	6.00
225 / 75R17.5	TL	129 / 127L	16	783	226	168	13	6.75





SSR05B

Long Haul / Regional Application, Steer Axle

- Excellent handling for maximum safety through customized tread pattern and casing design
- Maximized life expectancy and uniform wear through even pressure distribution in the ground contact patch
- Reduced rolling resistance and low fuel consumption, due to special tread compounds
- Featured groove design avoids stone trapping

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
9.5R17.5	TL	129 / 127L	16	842	240	182	13	6.75
235 / 75R17.5	TL	132 / 130M	16	797	233	188	13	6.75






SSD08

DESIGNED AND BUILT FOR DRIVING POSITION

- Superior mileage and excellent traction due to deep and aggressive pattern design
- Excellent self cleaning properties due to pattern characteristics and diamond shaped belt
- Maximum wet grip due to special formulated compound and extra block siping
- Several life cycles ensured by a highly durable casing construction

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
11R22.5	TL	148 / 145M	16	1056	279	210	18	8.25
12R22.5	TL	152 / 148M	16	1095	300	224	20	9.00
295 / 60R22.5	TL	149 / 146L	16	934	292	250	20	9.00
315 / 60R22.5	TL	152 / 148L	16	960	313	272	20	9.75
315 / 70R22.5	TL	152 / 148M (154 / 150L)	18	1030	312	278	21	9.00
295 / 80R22.5	TL	152 / 148M	16	1060	298	250	21	9.00
315 / 80R22.5	TL	156 / 150L (154/150M)	20	1090	312	256	21	9.00




SSD08B

Long Haul / Regional Application, Drive Axle

- Superior mileage and excellent traction due to deep and aggressive pattern design
- Excellent self cleaning properties due to pattern characteristics and diamond shaped belt
- Maximum wet grip due to special formulated compound and extra block siping
- Several life cycles ensured by a highly durable casing construction

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
215 / 75R17.5	TL	126 / 124L	16	767	212	168	15	6.00
245 / 70R19.5	TL	136 / 134M (141 / 140J)	16	839	248	190	15	7.50






SSM10

DESIGNED AND BUILT FOR DRIVING POSITION

- Optimum resistance to damage due to a new on/off road compound and new casing contour
- Robust pattern design to suit harsh on/off road conditions
- Excellent retreadability and structural strength due to reinforced belt design and durable casing
- Excellent traction due to deep and aggressive pattern design

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
13R22.5	TL	154 / 150K (156 / 150G)	18	1124	320	254	20	9.75
315 / 80R22.5	TL	156 / 150L (154/150M)	20	1088	312	256	20	9.00
295 / 80R22.5	TL	152 / 148M	16	1058	298	250	20	9.00






SST22

On / Off Application, Drive Axle

- Superior mileage due to high tread volume combined with special formulated compound
- On/off road design for all position application
- Good retreadability due to strong casing
- Stone ejector in all grooves eliminates casing damage

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
13R22.5	TL	154 / 150K (156 / 150G)	18	1124	320	254	18	9.75








SSR055A/*SSR55A+

Long Haul / Regional Application, Steer Axle

- Provides excellent traction
- Solid shoulder construction eliminates shoulder wear
- High hardness tread rubber for long mileage

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
385 / 55R22.5	TL	160K (158L)	20	996	386	290	15	12.25
385 / 65R22.5	TL	160K (158L)	18	1072	389	288	15	11.75
*385 / 65R22.5	TL	160K (158L)	18	1072	389	288	15	11.75
425 / 65R22.5	TL	165K	20	1124	430	320	15	13.00
445 / 65R22.5	TL	169K	20	1150	444	350	17	14.00





SSR065

Long Haul / Regional Application, Trailer

- 5 straight rib design with minimum splices ensures even wear to enhance long tyre life.
- Wide and straight grooves evacuate water on wet road.
- Wide steel-belt construction braces the tread and high-resilient steel filler balances stiffness of the casing for improved durability.

INFLATED NEW TYRE DIMENSIONS

	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
385 / 65R22.5	TL	160K (158L)	18	1072	389	290	15	11.75







SST066

Long Haul / Regional Application, Drive or Trailer

- Superior mileage due to high tread volume combined with special formulated compound
- On road design for all position application
- Good retreadability due to strong casing
- Stone ejector in all grooves eliminates casing damage

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
385 / 65R22.5	TL	160K (158L)	18	1080	389	288	18	11.75
425 / 65R22.5	TL	165K	20	1130	430	320	18	13.00
445 / 65R22.5	TL	169K	20	1156	444	320	20	14.00






SSM07/*SSM07A

DESIGNED FOR ALL-POSITION USE

- Excellent all-position performance
- Special chip and cut resistant compound
- Superior durability with reinforced belt design and durable casing
- High mileage due to special formulated compound

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
900R20	TT	144 / 142L	16	1022	259	185	16.5	7.00
1000R20	TT	146 / 143L	16	1049	272	214	17	7.50
1100R20	TT	150 / 147L	18	1088	286	223	17.5	8.00
1200R20	TT	154 / 151L	18	1123	307	240	18	8.50
*11R22.5	TL	148/ 145M	16	1054	279	214	17	8.25
*12R22.5	TL	152 / 148M	16	1084	300	230	17	9.00
*295 / 80R22.5	TL	152 / 148M	16	1054	298	252	18	9.00
*315 / 80R22.5	TL	156 / 150L (154/150M)	20	1084	312	258	18	9.00






SSU05

Urban Bus Application, All Axle

- High Resistance to irregular wear
- Outstanding Mileage
- Reinforced sidewall provides protection against kerb damage
- Several life cycles ensured by a highly durable casing construction

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
275 / 70R22.5	TL	148 / 145J(152 / 148F)	16	970	276	235	19.5	8.25




SSU500

Urban Bus Application, All Axle

- Specially designed tread pattern for good grip
- Outstanding Mileage
- Reinforced sidewall provides protection against kerb damage

INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
305 / 70R22.5	TL	152 / 148J (154 / 150E)		1000	305	250	20	9.00





SML68/*SML68A

DESIGNED FOR MINING AND LOGGING

- Aggressive pattern design to operate under severe conditions in off-road applications
- Superior durability with reinforced belt design and extra durable casing
- Excellent traction due to deep block pattern with self cleaning effects
- Chip and chunk resistant compound



INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
1200R24	TT	160 / 157L	20	1226	313	240	24	8.50
*1000R20	TT	149 / 146K	18	1054	278	221	20.5	7.50
*1100R20	TT	152/ 149K	18	1096	293	230	21	0.50
*1200R20	TT	156/ 153J	18	1136	315	231	21.5	8.50
*295 / 80R22.5	TL	152 / 149L	18	1050	298	240	22	9.00
*13R22.5	TL	154/ 151L	18	1124	320	240	22	9.75



SML68XL / *SML68B

Off Road Application, Steer or All Axle

- Aggressive pattern design to operate under severe conditions in off-road applications
- Superior durability with reinforced belt design and extra durable casing
- Excellent traction due to deep block pattern with self cleaning effects
- Chip and chunk resistant compound



INFLATED NEW TYRE DIMENSIONS

Size	TT / TL	LI & SS	P.R.	O.D.	S.W.	T.W.	NSD	Rim Width (inch)
1000R20	TT	149 / 146F	18	1065	280	210	23.5	7.50
1100R20	TT	152 / 144F	18	1096	295	220	24.5	8.00
*11R22.5	TL	148 / 145J	16	1065	279	210	25	8.25
*12R22.5	TL	152 / 149M	18	1084	300	226	25	9.00





19 Lok Yang Way, Jurong Singapore 628635

T: +65 6268 3111

F: +65 6264 0148

E: sales@sumotire.com

W: www.sumotire.com

* SUMO FIRENZA tyres are not offered or available for sale in the USA