



SUMO TIRE



SUMO TIRE

19 Lok Yang Way, Jurong Singapore 628635

T : +65 6268 3111 F : +65 6264 0148 E : sales@sumotire.com

www.sumotire.com

SUMO
**PORTMASTER
INDUSTRIAL**
TYRES



E-3

E-3A

DESIGNED TO WITHSTAND HUGE LOADS WITH OCCASIONAL TURNING ON UNEVEN SURFACE IN PORTS

- Sturdy construction to resist damage
- Multiple layers of high-tech nylon
- Low rolling resistance
- Superior damping properties
- Outstanding maneuverability

PORTMASTER TECHNICAL SPECIFICATIONS

Size	Ply Rate	Pattern	Recommend Rim	Dimension (mm)			Inflation Pressure (kPa)	TL / TT
				Width	T.D	O.D		
16.00-25	32	E-3	11.25/2.0	430	36	1495	975	TL
21.00-25	42	E-3A	11.25/2.0	572	42	1750	1150	TL



E-4

IND-4

E-4A

DESIGNED FOR PORT USE WITH OPERATOR COMFORT. TYRES ARE ABLE TO WITHSTAND HEAVY LOADS UNDER DEMANDING CONDITIONS OF MANEUVERABILITY, SPEED AND HEIGHT

- Sturdy construction to resist damage
- Multiple layers of high-tech nylon
- Low rolling resistance
- Tread design suitable for uneven surface
- Outstanding maneuverability
- Resistance to UV degradation (cracking)

PORTMASTER TECHNICAL SPECIFICATIONS

Size	Ply Rate	Pattern	Recommend Rim	Dimension (mm)			Inflation Pressure (kPa)	TL / TT
				Width	T.D	O.D		
16.00-25	36	E-4	11.25/2.0	432	62	1548	1150	TL
16.00-25	32	E-4	11.25/2.0	432	62	1548	1000	TL
16.00-25	28	E-4	11.25/2.0	432	62	1548	900	TL
18.00-25	40	IND-4	13.00/2.5	515	55	1673	1150	TL
14.00-24	28	E-4A	10.0	375	40	1370	1000	TT